

# MATERIAL SAFETY DATA SHEET

Product Name: EX-3 Stain  
MSDS No EX-3 Stain (J2005-G2)E ,Ver1.2  
Revised: 1<sup>st</sup> April, 2012

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1 Product identifier

Trade name/designation Noritake Super Porcelain EX-3 / External Stain, Internal Stain, ES Glaze

### 1.2 Relevant identified uses of the substance or mixture and uses advised

Relevant identified uses Dental Material

Uses advised against No information

### 1.3 Details of the supplier of the safety data sheet

#### • Manufacturer:

Kuraray Noritake Dental Inc.  
300 Higashiyama, Miyoshi-cho, Miyoshi, Aichi 470-0293, Japan

#### • Supplier:

##### For US

Kuraray America, Inc.  
33 Maiden Lane, 6th Floor, New York, NY 10038 U.S.A.  
Phone: 800-879-1676 Fax: 888-700-5200  
Website: www.kuraraydental.com

##### For Europe

Kuraray Europe GmbH  
Philipp-Reis-Str. 4, 65795 Hattersheim am Main, Germany  
Phone: +49 (0)69 305 35 840 Fax: +49 (0)69 305 35 640  
E-mail: dental@kuraray.de

##### For Other countries

Kuraray Noritake Dental Inc.

• Information department: Supplier

## 2. HAZARDS IDENTIFICATION

### 2.1 Classification of the mixture

#### GHS classification

Acute Tox.4	H302
Res. Sens. 1	H334
Skin Sens. 1	H317
Carc. 1A	H350
STOT SE 2	H371
STOT RE 2	H373

### 2.2 Label elements

#### Hazard pictograms



#### Signal word:

Danger

#### Hazard statements:

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H350 May cause cancer.

# MATERIAL SAFETY DATA SHEET

Product Name: EX-3 Stain  
MSDS No EX-3 Stain (J2005-G2)E ,Ver1.2  
Revised: 1<sup>st</sup> April, 2012

H371 May cause damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

## Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until at safty precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash throughly after handling.

P270 Do not eat,drink or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective glove/protective clothing/eye protection/face protection.

P281 Use Personal protective equipment as required.

P285 In case of inadequate ventilation wear respiratory protection.

P301+P312 If swallowed: Call a POISON CENTER or doctor/physician if you feel unwell.

P302+P352 If on skin: Wash with plenty soap and water.

P304+P341 If inhaled: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313 If exposed or concerned: Get medical advice/attention.

P309+P311 If exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment(see first aid statements on this label).

P330 Rinse mouth.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms:Call a POISON CENTER or doctor/physician.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/innternational regulation.

## **3.COMPOSITION / INFORMATION ON INGREDIENTS**

3.1 Description of the mixture:

3.2 Hazardous ingredients:

CAS No.	EC-No.	MITI-No.	% (w/w)	name	Remark
18186-89-0*		1-267 1-517 1-550	<3	COBALT NICKEL GRAY PERICLASE(CPMA)	*

\*Substance classified by the manufacture.

## **4.FIRST AID MEASURES**

4.1 Description of first aid measure

If on skin Wash with plenty soap and water.

If inhaled If breathing is difficult,remove victim to fresh air and keep at rest in a position comfortable for breathing.

If swallowed Call a POISON CENTER or doctor/physician if you feel unwell.

If in eyes Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

4.2 Most important symtoms and effects, both acute and delayed.

No information

4.3 Indication of immediate medical attention and special treatment needed.

No infomation

# MATERIAL SAFETY DATA SHEET

Product Name: EX-3 Stain  
MSDS No EX-3 Stain (J2005-G2)E ,Ver1.2  
Revised: 1<sup>st</sup> April, 2012

---

## 5. FIRE-FIGHTING MEASURES

---

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water-spray, CO<sub>2</sub>, powder, sand or foam, etc.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

#### Unusable extinguishing media

No information available.

### 5.2 Special hazards arising from the substance or mixture

Hazardous combustion products There is a possibility that the gas with stimulation or toxicity is produced depending on the kind of a fire.

### 5.3 Advice for fire-fighters

If it is not very dangerous, move containers from a fire in the surrounding area.

During extinction, wear a suitable heat-resistant protective suits against chemicals and self contained breathing apparatus.

Extinguish fire by pouring or spreading extinguishing media on the origin of a fire.

Extinguish fire from windward side as much as possible.

Extinguish fire by the method of covering tightly or suffocation is preferable.

Even after extinction, cool down containers by using plenty of water.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### 6.1 Personal precautions, protective equipment and emergency procedures

#### For non-emergency

Protective equipment Operators wear suitable protective equipment refer to section 8 and avoid inhalation and contact with eyes and skin.

Removal of ignition sources, provision of sufficient ventilation, control of dust

Ventilate for exhaust to keep concentration in air below a limit of exposure.

Emergency procedures Isolate this product immediately and keep proper distance to every direction as released area.

Indicate that only authorized people can enter.

Do not touch released product and walk on it.

#### For emergency responders

No information

### 6.2 Environmental Precautions

Take notice not to discharge this product to rivers etc. and not to affect environment.

### 6.3 Methods and material for containment and cleaning up

For containment No information.

For cleaning up If the amount of leakage is small, absorb it by dried sand, soil, sawdust and waste paper and collect it into a tightly covered container made of metal.

Other information No information

### 6.4 Reference to other sections See section 8 and 13.

### 6.5 Additional information No information.

---

## 7. HANDLING AND STORAGE

---

### 7.1 Precautions for safe handling

#### Information on safe handling

Take measure against equipments written in section 8 and wear protective equipment.

Exhaust locally and ventilate totally as written in section 8.

# MATERIAL SAFETY DATA SHEET

Product Name: EX-3 Stain  
MSDS No EX-3 Stain (J2005-G2)E ,Ver1.2  
Revised: 1<sup>st</sup> April, 2012

## To Prevent handling of incompatible substances or mixtures

Avoid contact with incompatible materials. Please refer to section10.

## To minimize the release to the environment

Take notice not to discharge this product to rivers etc. and not to affect environment.

## Advice on general occupational hygiene

Obtain Instructions before using this product.  
Do not handle products until you have read and understood every instruction for safety.  
To prevent exposure, wear protective during operation.  
Watch out for fire.  
Prohibit using heated substances, sparks and fire on the periphery of this product.  
Ventilate for exhaust to keep concentration in air below a limit of exposure.  
Avoid inhaling dust and fume.  
Do not touch, inhale or swallow this product.  
Do not take polluted work clothes out of workshops.  
Do not drink, eat or smoke during using this product.  
Use this product only outside or well ventilated area.  
Wash hands well after handling this product.  
Avoid emitting this product to environment.

## 7.2 Conditions for safe strage, including any incompatibilities

### Technical measures and storage conditions

Store in dried and properly ventilated place.  
Install equipments for lighting and ventilation which are necessary for handling and storing dangerous goods in a storage place.

### Packaging materials

If containers are stipulated in transportation regulations of containers United Nations.

### Requirements for storage rooms and vessels

Store apart from dangerous substance to mix and touch.  
Seal a container and store it in a well ventilated and cool place.  
It is preferable to store a container in a locked place.

### Further Information on storage conditions

No information

## 7.3 Specific end use(s)

### Recommendations

No information

### Industrial sector specific solutions

No information

## **8.EXPOSURE CONTROLS/PERSONAL PROTECTION**

### 8.1 Control parameters

#### Occupational Exposure limit values

Chemical Name	Class	Exposure Limits	BASIS
Dust	Class3	Respirable dust 2mg/m <sup>3</sup> Total dust 8mg/m <sup>3</sup>	Japan Society for Occupational Health (2009)
COBALT NICKEL GRAY PERICLASE(CPMA)	Nickel compounds	As Ni 0.1mg/m <sup>3</sup> Tot	Ministry of Labor( Japan)
	Cobalt and compounds	As Co 0.05mg/m <sup>3</sup>	Japan Society for Occupational Health (2009)
	Cobalt,Elemental and inorganic compounds	As Co 0.02mg/m <sup>3</sup>	ACGIH
	Nickel,Insoluble compounds	As Ni 0.2mg/m <sup>3</sup>	

# MATERIAL SAFETY DATA SHEET

Product Name: EX-3 Stain  
MSDS No EX-3 Stain (J2005-G2)E ,Ver1.2  
Revised: 1<sup>st</sup> April, 2012

	Zirconium and compounds	As Zr 5mg/m3	
--	-------------------------	--------------	--

## 8.2 Exposure controls

### Appropriate engineering controls

when the mists are generated, the ignition source is made to seal up, and the exhaust device is installed. Install ventilation facility if dust and fume occurs during hot heated processes.

### Personal protection equipment

Eye and face protection : Use appropriate protectors for eyes.

Skin protection

Hand protection : Use appropriate protective gloves.

Body protection : Use appropriate protective clothes and masks if necessary.

Other protection : —

Respiratory protection : Wear appropriate respiratory protection.

Thermal hazards : —

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state, shape and colors etc.	White, Blown, Red, Blue Powder
Odor	No odor
pH	No data
Melting point/coagulation point	No data
Boiling point	No data
Flash point	No data
Explosive range	No data
Vapor pressure	No data
Vapor density(air=1)	No data
Relative density (density)	No data
Solubility	No data
Partition coefficient: octanol/ water	No data
Auto-ignition temperature	No data
Decomposition temperature	No data
Limit value of odor	No data
Vaporization speed (butyl acetate=1)	No data
Combustion Characteristics (solid and gas)	No data
Viscosity	No data

## 10. STABILITY AND REACTIVITY

### 10.1 Reactivity

Not in particular.

### 10.2 Chemical Stability

Stable, if it is use and a storage method described in this MSDS.

### 10.3 Possibility of hazardous reactions

Not in particular.

### 10.4 Conditions to avoid

Not in particular.

### 10.5 Incompatible materials

No data.

### 10.6 Hazardous decomposition product

No data.

# MATERIAL SAFETY DATA SHEET

Product Name: EX-3 Stain  
MSDS No EX-3 Stain (J2005—G2)E ,Ver1.2  
Revised: 1<sup>st</sup> April, 2012

## 11. TOXICOLOGICAL INFORMATION

---

- 11.1 Acute Toxicity  
Harmful if swallowed.  
Mixture ATE  
ATE(oral) = 923mg/kg
- 11.2 Skin corrosion/irritation  
No information available
- 11.3 Serious eye damage/irritation  
No information available
- 11.4 Respiratory or skin sensitization  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction.  
As COBALT NICKEL GRAY PERICLASE(GPMA)  
Resp.Sens.1, Skin Sens.1 by manufacturer MSDS
- 11.5 Germ cell mutagenicity  
No information available
- 11.6 Carcinogenicity  
May cause cancer.  
As COBALT NICKEL GRAY PERICLASE(GPMA)  
Carc.1A by manufacturer MSDS
- 11.7 Reproductive toxicity  
No information available
- 11.8 STOT—single exposure  
May cause damage to organs  
As COBALT NICKEL GRAY PERICLASE(GPMA)  
STOT SE 1,2 by by manufacturer MSDS
- 11.9 STOT—repeated exposure  
May cause damage to organs through prolonged or repeated exposure.  
As COBALT NICKEL GRAY PERICLASE(GPMA)  
STOT RE 1 by manufacture MSDS
- 11.10 Aspiration hazard  
No information available

## 12. ECOLOGICAL INFORMATION

---

- 12.1 Toxicity  
No information available
- 12.2 Persistence and degradability  
No information available
- 12.3 Bioaccumulative potential  
No information available
- 12.4 Mobility in soil  
No information available
- 12.5 Other adverse effects  
No information

## 13. DISPOSAL CONSIDERATIONS

---

- 13.1 Waste treatment methods  
Product/ Packaging disposal In disposal, follow relevant regulations and standards of municipalities.  
If industrial waste disposer permitted by governors or regional public

# MATERIAL SAFETY DATA SHEET

Product Name: EX-3 Stain  
MSDS No EX-3 Stain (J2005-G2)E ,Ver1.2  
Revised: 1<sup>st</sup> April, 2012

organization handle disposition, commit it to them.  
If you commit a disposal of waste, notify sufficiently disposer of risk and harmfulness beforehand.  
Clean and recycle containers or dispose them properly based on relative regulations and standards of municipalities.  
When empty containers are disposed, its content must be removed completely.  
Dispose of waste according to applicable local, state, federal laws and regulations.  
Do not discharge to a water source.  
No informaton

## Waste treatment options

## Sewage disposal options

## Other disposal recommendations

### 13.2 Additional information

No information

## **14. TRANSPORT INFORMATION**

Road/Rail(ADR/RID) Not subject to ADR/RID.  
Sea transport(IMDG) Not subject to IMDG code.  
Air transport(IATA) Not Subject to IATA regulations.

## **15. REGULATORY INFORMATION**

This MSDS is according to Globally Harmonized System of Classification and Labelling of Chemicals (GHS).  
Use in accordance with local/regional/national/international regulations.

## **16. OTHER INFORMATION**

### 16.1 Indication of changes and preparation date

Preparation date 14th October, 2010  
Revised 14th October, 2010

### 16.2 Abbreviations and acronyms

ACGIH American Conference of Governmental Industrial Hygienists  
ATE Acute Toxicity Estimate  
CAS No. Chemical Abstract Service number  
EC No. EINECS and ELINCS Number  
EINECS European Inventory of Existing Commercial Substances  
ELINCS European List of notified Chemical Substances  
GHS Globally Harmonized System  
LC50 Lethal concentration, 50%  
LD50 Median Lethal Dose  
MSDS Material Safety Data Sheet  
MITI No. Ministry of International Trade and Industry Number  
NITE National Institute of Technology and Evaluation  
OEL Occupational Exposure Limit  
STOT Specific Target Organ Toxicity  
(STOT) RE Repeated Exposure  
(STOT) SE Single Exposure  
TWA Time Weighted Average

# MATERIAL SAFETY DATA SHEET

Product Name: EX-3 Stain  
MSDS No EX-3 Stain (J2005-G2)E ,Ver1.2  
Revised: 1<sup>st</sup> April, 2012

---

## 16.3 Key literature references and sources for data

The result of classification of substance by NITE Japan. (<http://www.safe.nite.go.jp/ghs/list.html>)

## 16.4 Handling of information given in this MSDS

Information given in this MSDS may be insufficient for not all records and references were investigated. Its content can be changed due to release of new data and correction of conventional theories. Therefore, when you use this MSDS for an important decision, it is recommended to check its content by running tests or to study its references carefully. We also do not guarantee the number about the content, physical or chemical properties. Notes are applicable to normal handling and care must be taken in case of special handling.